

Features & Benefits

Unlimited cutting depth

No vibration or noise and fast cutting speed

Modular design provides infinite setup options

Bases mount to concrete surface with anchor bolts

Includes

- (1) 8ft. column,
- (1) 32" drive wheel,
- (3) mounting bases,
- (4) 16" idler wheels,
- (2) universal clamps,
- (1) 11ft. (1) 6ft

and (4) 3ft. schedule 80 pipe sections





Specifications

Wire Speed: 0-5,000 ft/min - infinitely variable and reversible

Drive Motor: 6 ft. stroke driven by Danfoss 1.93 cubic inch hydraulic motor

Sawing Angle: Set up vertical or horizontal from the same frame **Drive Motor:** Char-Lynn 9.9 cubic inch hydraulic motor

525 rpm @ 25 gpm

Drive Wheel: 32" diameter with neoprene lining in 'V' groove

Idler Wheels: 8", 10" and 16" special polyethylene wheels with sealed bearings

8" idler adapts to the end of 2" pipe

10" and 16" idlers have 1-3/16" shaft for use with universal clamps

Pipe Mounting: For use with 2" schedule 80 pipe



BS-2 Hydraulic Remote Control Unit



WS25 WIRE SAW		
Description	Part #	Cat #
WS25 Wire Saw for use with BS2	5800061	02248
WS25 Wire Saw for use with Control Station	5800669	09484
WS25 Flush Cut Wire Saw for Use with BS2	5800621	50169
WS25 Flush Cut Wire Saw for Use with Control Station	5800622	39314
Wire Saw Control Station	5800059	02247
BS-2 Remote Control Unit (Single Pump) with 25' hoses	5800112	48601
WS25 ACCESSORIES		
16" idler wheel	6020025	02581
10" idler wheel	6020035	02583
Universal clamp	6020020	02578
Pipe mounting base	6020000	02565
24" drive wheel	6020051	79330
32" drive wheel	6020052	79331

Parts List: 1800292

Flush Cut Parts List: 1801027 Operator Manual: 1800760

