

# Husqvarna Husqvarna K 960 Ring

The Husqvarna K 960 Ring is the world's first petrol-powered cutter to be able to make 260 mm deep cuts with a 350 mm blade. This may seem impossible to anyone who uses standard power cutters, since 350 mm blades can normally only achieve a cutting depth of 125 mm. However, we have quite simply combined our unique - and patented - RingSaw technology, where the blade is driven from the periphery instead of its centre, with the strong, easy to handle petrol-powered cutter, the Husqvarna K 960. With the K 960 Ring, you can have the best of both worlds: the tried and tested ringsaw technology with its incredible cutting depth, and the ease of use and versatility of a petrol-powered cutter.



*Huge potential - By using K 960 Ring on pipe diameter up to 260 mm, the cut can be made from one position. This saves a lot of unnecessary digging which, in turn, saves time and money with less filling and finishing work.*



*Active Air Filtration™ - The Active Air Filtration™ has been upgraded with a redesigned paper filter, for even better dust control.*



*SmartCarb™ - Built-in automatic filter compensation, maintains high power and lowers fuel consumption.*



*DuraStarter™ - Patented, dust-sealed starter unit, where the return spring and the pulley bearing are sealed. This makes the starter virtually maintenance free, giving a further boost to the reliability of our cutters.*

- EasyStart ensures 50% easier starting by reducing the compression in the cylinder during starting.
- All our cutters except the K 3000 Electric feature our robust new wet cutting kit, with low water usage.
- Sealed transmission reduces the wear and slippage risk.
- Self-lubricating clutch bearings for extended work life.
- Easy-adjust blade guard
- Twice the cutting depth of traditional style blades.
- Folding blade and splash guard facilitate cutting close to ceilings and walls.
- Easy adjustment of blade and rollers.
- Easy cleaning simplifies service and maintenance.

## Technical Data

SPECIFICATIONS	Husqvarna K 960 Ring
Cylinder displacement	5.7 cu.inch
Max cutting depth	10 inch
Weight (excl. cutting equipment)	28.8 lbs
Vibrations front handle	3.5 m/s <sup>2</sup>
Vibrations rear handle	3.7 m/s <sup>2</sup>
Sound level	104 dB(A)
Sound power level, LWA	118 dB(A)